

为时尚产业 提供智能制造解决方案

*Intelligent manufacturing
Solutions for fashion industries*

SP-460AS-HF 厚料气动

SP-460AS-MF 中厚料气动

SP-860AS-HF 厚料气动

SP-860AS-MF 中厚料气动

电子套结机
Electronic Bartack Machine



- 改善了夹线系统，即使缝纫开始时不减速也可防止产生面线脱线；
- 缩短切线后针线余线，可有效防止在缝纫开始时出现鸟巢状线迹，进一步提高了缝纫品质；
- 无油式针杆，可杜绝缝料的污染；
- 高转速
最高转速3200 rpm，完全按照缝制数据进行高质量缝纫；
- 耗电少
采用无传动损失的电脑直接驱动方式，并装备了小型节电马达；
耗能量与传统机型比削弱了35%。
- 触摸屏操作面板，完全可视化的人机界面，只需手指轻触即可完成人机对话，根据图标可快速简便的编辑缝纫花样。

- Improved thread catching device can reduce thread falling off from needle even without slowing down the sewing speed at beginning,
- Shortening the remained thread after trimming can efficiently reduce the bird nest appearing at beginning of the sewing, which improves sewing quality.
- Oil-free needle bar prevents pollution of material
- Higher speed
Maximum speed 3200rpm, Quality sewing based on sewing pattern
- Lower power consumption:
Adoption of no transmission lost computer direct drive manner, equipped with small energy saving motor, Power consumption reduced by 35% compared with the traditional machines.
- Touch screen operation panel, visible HMI, editing the patterns easily only by fingers touching on icons.



压脚驱动方式



S：压脚电磁式驱动
Pressure foot solenoid-driven

Foot clamp drive mode



压脚气动式驱动
Pressure foot Pneumatically-driven

采用SMC气缸
SMC cylinder

选购件



Optional

钉扣纽夹装置
Button clamp device

舒普套结机可直接更换纽夹装置，更换便捷，可实现一机多用，套结及钉扣功能。
Button clamp device can be used on supreme bartack machine easy to install and replace to achive multi-purpose for barcack and button stitching.

规格 Specification

型号Model	SP-460AS		SP-860AS	
用途Application	小范围花样缝制 Electronic Pattern Sewing Machine			
线迹Line	单针平缝Single-needle flat seam			
最高缝纫速度 Maximum Speed	3,200 rpm			
缝制区域(X×Y) Sewing area	40×60mm		80×60mm	
送布装置Feeding Method	间歇送布（脉冲马达驱动） Intermittent feeding (driven by pulse motor)			
针距 Pitch	0.1 - 12.7mm			
最大针数 Maximum stitch amount	5000针/1个图案(5000 needles/1 pattern)			
抬压脚方式 Driven Method	气动Pneumatic			
压脚上升量 Presser foot stroke	最大Max.17mm			
旋梭Hook	半回转标准摆梭 / Semi-Rotary standard shuttle hook			
扫线装置 Thread Wiper	标准装备 / Standard facility			
切线装置Cutting device	标准装备 / Standard facility			
外部数据储存媒体 External data storage media	USB			
循环程序数 Number of cycle programs	30 个循环 (各 50 个程序) / 30 cycles (50programs for each)			
存储数据数 Number of stored data	89 种缝纫图案 / 89 patterns 最多可追加 512 种图案，追加总针数约 500,000 针 / Maximum 512 patterns more ,estimated 500000 stitches			
马达Motor	AC伺服马达550W/ AC servomotor 550W			
机器尺寸 Machine size	600×260×470		600×260×470	
包装尺寸Packing size	710×450×550		710×450×550	
重量Weight	55kg		55kg	
电源Power	单相220V Single phase 220V			
气压Air pressure	0.5 Mpa 1.7 L/min			

以上型号仅供参考，详细情况请咨询当地经销商。
The above types are only for reference, and you can consult local distributors for details.

为了改良，产品规格若有变更，恕不另行通知。为安全起见，使用之前，请仔细阅读使用手册。
Specifications are subject to change for improvement without further notice. Please carefully read the operating manual before use for safety.